

BW CCTV MONITOR



MM-9A



MM-12A

Model	MM-9A	MM-12A
Picture Tube	9" diagonal B/W	12" diagonal B/W
Horizontal Resolution	>800 TV lines (Center)	
Scanning Frequency	15.625 KHz/50Hz (CCIR)	
Video Input	1.0Vp-p / 75 ohm	
Video Connections	BNC (in x 1) / (out x1)	
Audio Connections	RCA (in x 1) / (out x 1)	
Power Input	AC 100 ~ 240V, 50/Hz	
Power Consumption	20 W	30 W
Dimension (mm)	222(W)x243(H)x250(D)	304(W)x320(H)x310(D)
Weight (Kg)	4.5	8.0
Operating Temperature Range	-10°C ~ +50°C	



MM-15A



MM-20A

Model	MM-15A	MM-20A
Picture Tube	15" diagonal B/W	20" diagonal B/W
Horizontal Resolution	>1000 TV lines (Center)	
Scanning Frequency	15.625 KHz/50Hz (CCIR)	
Video Input	1.0Vp-p / 75 ohm	
Video Connections	BNC (in x 1) / (out x1)	
Audio Connections	RCA (in x 1) / (out x 1)	
Power Input	AC 100 ~ 240V, 50/60 Hz	
Power Consumption	35 W max	36 W max
Dimension (mm)	350(W)x350(H)x360(D)	472(W)x450(H)x360(D)
Weight (Kg)	12	20
Operating Temperature Range	-10°C ~ +50°C	

