

IPE540 & IPE540-W

FEATURES :

- Small Compact Size
- MPEG-4 Compression Format
- 2-Way audio
- Support cell phone/PDA/3GPP
- Dual Streaming
- Wireless (IPE540-W Only)
- Free Bundle 36 Channel Recording Software



MPEG-4



DUAL STREAMING



2 WAY AUDIO



CELL PHONE/
3GPP



WIRELESS
(IPE540-W)



SPECIFICATION :

Hardware	
CPU	ARM 9, 32 bit RISC
RAM	32 MB
ROM	8 MB
Image Sensor	1/4" CMOS
Sensitivity	1.5 lux @ F2.0
Lens Type	4.0 mm, F2.0
Audio Out	1 (3.5 mm Phone Jack)
Power Consumption	LAN : DC 12V, 0.2A WLAN : DC 12V, 0.25A
Operating Temperature	-10°C ~ 45°C
Dimensions (mm)	59 x 93.7 x 45.5
Weight (g)	180
Network	
Ethernet	10/100 Base T
Wireless	802.11b/g (optional) (only IPE540-W)
WEP	64/128 bit
Network Protocol	HTTP, TCP/IP, UDP, SMTP, FTP, PPPoE DHCP, DDNS, NTP, 3GPP, UPnP

System	
Video Resolution	640 x 480, 320 x 240, 160 x 120
Video Adjust	Brightness, Contrast, Exposure, Sharpness, AGC, Night Mode
Dual Streaming	Yes
Image snapshot	Yes
Full screen monitoring	Yes
Compression format	MPEG-4
Video bitrate adjust	CBR, VBR
Motion Detection	Yes, 3 different areas
Triggered action	Mail, FTP
Pre / Post alarm	Yes, configurable
Security	Password protection
Firmware upgrade	HTTP mode, can be upgraded remotely
Simultaneous connection	up to 10
Audio	Yes, 2-way (Duplex Support)
Client System requirements	
OS	Windows 2000, XP, 2003, IE 6 or above
Hardware	
Suggested	Intel-C2.6G, RAM : 512MB, Graphic card : 64MB
Minimum	Intel-C1.6G, RAM : 256MB, Graphic card : 32MB