

4 / 8 / 16 CH H.264 DVR

NDR402, NDR803-D, NDR 1603-D

TelView



NDR402



NDR803-D



NDR1603-D

Features

- H.264 Hardware video Compression.
- 240 PPS.
- ICR (IE Remote Control); User Can Setup DVR from IE Browser.
- Recording quality / rate adjustment per channel available.
- Support CMS (Central Management System)/3GPP.
- Audio Backup / Audio Streaming.
- Graphic User Interface (GUI).
- Support time-point backup function under ethernet remote control mode.
- User can select any time period to process backup from remote side.
- Support time-search & event-search function under Ethernet remote control mode.
- Up to four online clients for independent remote control; Individual live-time, playback & time-search function available.
- Support PPPoE / Static / DHCP IP & DDNS.
- Real Triplex recording / live-time & playback operation at the same time available.
- ID function supplied from IR remote controller, User can control different DVRs at the same time by using one IR remote controller.




BlackBerry-Bold

Application



Container Yard



Hotel



Harbor



Air Port



Train Station

Specification

Model	NDR402		NDR803-D		NDR1603-D	
VIDEO						
Mode	Triplex					
Image System	NTSC / PAL					
Live-time Resolution	NTSC : 720 x 480 PAL : 720 x 576					
Live-time Display rate	4x30 Frame/sec	4x25 Frame/sec	8x30 Frame/sec	8 x 25 Frame/sec	16 x 30 Frame/Sec	16 x 25 Frame/Sec
Split Screen	1.4		1,4,9		1,4,9,13,16	
Video Input	BNC x 4		BNC x 8		BNC x 16	
Video Looping	No		No		BNC x 16	
Video Output (BNC)	BNC x 1		BNC x 1		BNC x 1	
Video Output (Spot Monitor)			No		BNC x 1	
AUDIO						
Audio Input	RCA x 1					
Audio Output	RCA x 1					
Audio Backup	Yes					
RECORDING						
Recording Type	H.264					
Recording Rate (D1)	NTSC : 720 x 480 up to 30 PPS PAL : 720 x 576 up to 25 PPS		NTSC : 720 x 480 up to 60 PPS PAL : 720 x 576 up to 50 PPS		NTSC : 720 x 480 up to 60 PPS PAL : 720 x 576 up to 60 PPS	
Recording Rate (Half D1)	NTSC : 720 x 240 up to 60 PPS PAL : 720 x 288 up to 50 PPS		NTSC : 720 x 240 up to 120 PPS PAL : 720 x 288 up to 100 PPS		NTSC : 720 x 240 up to 120 PPS PAL : 720 x 288 up to 100 PPS	
Recording Rate (CIF)	NTSC : 360 x 240 up to 120 PPS PAL : 360 x 288 up to 100 PPS		NTSC : 360 x 240 up to 240 PPS PAL : 360 x 288 up to 200 PPS		NTSC : 360 x 240 up to 240 PPS PAL : 360 x 288 up to 200 PPS	
STORAGE & BACKUP DEVICE						
Internal HDD Support	SATA HDD x 2					
External USB HDD Support	Yes					
CD/DVD RW Backup	Yes					
NETWORK						
Ethernet	Yes					
Ethernet Compression Format	H.264					
IE Remote Control	Yes					
Networking IP	Static / Dynamic / PPPoE					
ALARM						
Alarm Input	4 In (NO/NC)				16 In (NO/NC)	
Alarm Output	1 Out (NO/NC)					
Motion Detection	Yes					
Motion Detection Area	30 x 24 grids					
Motion Detection Sensitivity	1-100					
Video Loss Detection	Yes					
SETUP & OTHER FUNCTION						
PTZ Control	Yes					
RS-232	No				Yes	
RS-485	Yes					
Digital Zoom	Yes					
OTHERS						
Dimensions (mm)	218 (W) x 44 (H) x 202 (D)		360 (W) x 60 (H) x 311 (D)		430 (W) x 68 (H) x 382 (D)	
Weight (Kg)	1.4		3		6.3	

