

HIGH TECHNOLOGY TOUCH PANEL SWB Series

TelView



FEATURES

HIGH PERFORMANCE

- High Picture Quality
- Various Recording Modes : Motion, Alarm, Schedule, Continues, Dual Recording.
- Event log search, calender search
- SMART Network Transfer

EASY TO USE (Simple enough and intuitive)

- User Friendly GUI (True Color)
- Quick Setup
- Built-in Multiplexer and Pan / Tilt / Zoom / Focus Controller
- Mouse / IR Remote

WORRY-FREE

- Hardware Watch-Dog / Power Failure Recovery : Auto Reboot with Maintaining Previous Record Settings
- Alarm Notification (Max 5 Users): e-mail transmission
- Auto File Fix: Automatic file fix and recovery to compensate for possible fire corruption after power failure or abnormal system operation
- S.M.A.R.T HDD



BLACKBERRY
And all Handphone
COMPATIBLE



REAR PANEL



SWB 412



SWB 812



SWB 1612

SPECIFICATION

SYSTEM

Multiple Function	Quadruplex
OS	Embedded Linux
Video Input	4ch - SWB 412 / 8ch - SWB 812 / 16ch - SWB1612
Video Output	1 VGA, 1 Composite, 1 Spot
Audio Input / Output	1 in - 1 out (RCA)
Alarm Input / Output	4 in - 1 out - SWB 412 8 in - 1 out - SWB 812 16 in - 1 out - SWB 1612
Power	Adaptor DV 12V/3A

DISPLAY AND RECORDING

Compression	H.264
Data Size	0.06-0.86 Mbps/ch @30fps (CIF, Low~D1, Ultra)
Live Display Resolution	720 x 480 (NTSC) / 720 x 576 (PAL)
Live Display Speed	Real time
Display Split Mode	1, 4, 8, 16
Recording Speed	30fps 720x480(NTSC), 25fps 720x576(PAL) 60fps 720x240(NTSC), 50fps 720x288(PAL) 120fps 360x240(NTSC), 100fps 360x288(PAL)
Recording Mode	Continuous, Schedule, Motion, Alarm
Recording Quality	Low, Middle, High, Super, Ultra
Motion Detection	4 x 4 (SET), 28 x 24 Grids (CMS), 20 Sensitivity Levels

SEARCH & PLAYBACK

Search Method	Date & Time, Camera, Log Search
Playback of Backup file	Mini Player (Auto Copy), SMS
Playback Speed	Multi Level

BACKUP & STORAGE

Backup Storage Interface	1 x USB 2.0
External Backup Device	External HDD, Flash Memory Stick
Internal HDD	1 x HDD
DATA Archiving	Ethernet, Remote PC, External Recording Device

NETWORK & EVENT

Network Interface	RJ 45 / Ethernet
Network Line	LAN, WAN, Internet
Network Transmission Speed	Max 120fps
Alarm Notification	E-mail: Alarm, Video Loss, Power Loss, HDD Failure
Pre-Alarm / Post - Alarm	3 sec / 10 sec ~ 300 sec
DDNS Support	Unique, Public Method

MISCELLANEOUS

Controls	Mouse, IR remote, Front touch key, CMS, IE
Firmware Upgrade	USB Memory stick
Dimension	280(W) x 315(D) x 55 (H) mm
Weight	1.91 Kg without HDD (4.2 lbs)
Power Consumption	19.2 W (HDD 250 GB 1 EA)
Operation Temperature	0°C ~ 40°C

APPLICATION



Harbor



Train Station



Container Yard



Air Port



Hotel

TelView