

# VIDEO AUDIO SWITCHER

## VS41A / VS61A / VS81A



- Vertical inspection
- Low electricity, low noise
- Smd board
- 19" rack - mount available
- Bypass function for useless camera
- Home function will appoint sole camera
- Auto function is video automatically sequence

### SPECIFICATION

TYPE	VS41A	VS61A	VS81A
Video Inputs	1.0Vp-p/75 ohm, 4 Input	1.0Vp-p/75 ohm, 6 Input	1.0Vp-p/75 ohm, 8 Input
Audio Inputs	2Vp-p/10K ohm, 4 Input	2Vp-p/10K ohm, 6 Input	2Vp-p/10K ohm, 8 Input
Video Output	1Vp-p/75 ohm		
Audio Output	2Vp-p/10K ohm, MAX		
Video Gain	From attenuation to amplifier 0.8 Vp-p to 1.4Vp-p		
Video Bandwidth	20 MHz +3db to - 3db		
Cross talk	Better than 48db		
Channel Switch	BYPASS / AUTO / HOME		
Switching	Approx 1 to 15 sec		
Video Connector	BNC or F Connector		
Max Video Input	2.0Vp-p		
Power Lamp	Red LED		
Operation Temperature	- 5°C ~ 60°C		
Power Consumption	3 W		
Power Requirements	AC110V / 60Hz, AC230V / 50 Hz		
Construction	Steel, Gray enamel finish		
Dimensions	218 mm(W) X 44 mm(H) X 97 mm(D)		
Weight	810 g	820g	830g

